



data sheet

SILICONE RUBBER COATED FIBERGLASS TAPE

HVMT COPPER

Description

This is a high temperature, COPPER colored silicone rubber coated fiber glass cloth tape with a pressure sensitive silicone polymer adhesive on one side. The COPPER colored surface of the tape provides conformability and high face to back adhesion.

Features and Benefits

- ⇒ Excellent resistance to cut through and abrasion
- ⇒ Superior adhesion to itself to withstand the extreme conditions of HVOF coatings
- ⇒ Releases cleanly from metal surfaces.
- ⇒ Excellent resistance to grit blasting and abrasion resistance associated with HVOF coating operations.

PHYSICAL PROPERTIES

Product Number	H.V.M.T. Copper
Total Thickness (Nominal) mil	28
Tensile Strength (lbs. per inch of width)	300
Colour	Copper
Operating Temperature	-100°F to + 500°F
Adhesion to Steel (oz. per inch of width)	45
Adhesion to Itself (oz. per inch of width)	55
Width Available	1/2 inch to 18
Standard Roll Length	18 yards

All values shown herein are typical and are not to be considered specifications. In all instances, the user shall determine the suitability of any Green Belting Industries Limited's product for any given application.

"We Earn Your Business"

ISO 9001:2000 Registered

www.greenbelting.com

CONTROLLED